


SS52 THRU SS510

Surface Mount Schottky Barrier Rectifier

DO-214AA/SMB



Dimensions in inches and (millimeters)

FEATURES

- ◆ The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- ◆ For surface mounted applications
- ◆ Low reverse leakage
- ◆ Built-in strain relief, ideal for automated placement
- ◆ High forward surge current capability
- ◆ High temperature soldering guaranteed: 250°C/10 seconds at terminals

MECHANICAL DATA

Case: JEDEC DO-214AA molded plastic body
Terminals: Solder plated, solderable per MIL-STD-750, Method 2026

Polarity: Color band denotes cathode end

Mounting Position: Any

Weight: 0.005 ounce, 0.138 grams

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.


	SYMBOLS	SS52	SS53	SS54	SS55	SS56	SS58	SS510	UNITS
Maximum repetitive peak reverse voltage	V _{RRM}	20	30	40	50	60	80	100	VOLTS
Maximum RMS voltage	V _{RMS}	14	21	28	35	42	56	70	VOLTS
Maximum DC blocking voltage	V _{DC}	20	30	40	50	60	80	100	VOLTS
Maximum average forward rectified current at T _L (see fig.1)	I _(AV)	5.0							Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}	150.0							Amps
Maximum instantaneous forward voltage at 5.0A	V _F	0.55			0.70		0.85		Volts
Maximum DC reverse current at rated DC blocking voltage	I _R	0.5							mA
TA=25°C TA=100°C		20					10		
Typical junction capacitance (NOTE 1)	C _J	200							pF
Typical thermal resistance (NOTE 2)	RθJA	50.0							°C/W
Operating junction temperature range	T _J	-65 to +150					-65 to +175		°C
Storage temperature range	T _{STG}	-65 to +150							°C

Note: 1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.

2. P.C.B. mounted with 0.2x0.2" (5.0x5.0mm) copper pad areas

AVERAGE FORWARD RECTIFIED CURRENT,
AMPERES

FIG. 1- FORWARD CURRENT DERATING CURVE



PEAK FORWARD SURGE CURRENT,
AMPERES

FIG. 2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT





FIG. 3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS



INSTANTANEOUS REVERSE CURRENT,
MILLIAMPERES

FIG. 4-TYPICAL REVERSE CHARACTERISTICS






FIG. 5-TYPICAL JUNCTION CAPACITANCE





TRANSIENT THERMAL IMPEDANCE,
°C/W

FIG. 6-TYPICAL TRANSIENT THERMAL IMPEDANCE



Packaging

Tape	<table> <tr> <th>Symbol</th><th>Dimension (mm)</th></tr> <tr><td>W</td><td>12.00±0.20</td></tr> <tr><td>P0</td><td>4.00±0.10</td></tr> <tr><td>P1</td><td>8.00±0.10</td></tr> <tr><td>P2</td><td>2.00±0.10</td></tr> <tr><td>D0</td><td>Φ1.55±0.10</td></tr> <tr><td>D1</td><td>Φ1.5±0.10</td></tr> <tr><td>E</td><td>1.75±0.10</td></tr> <tr><td>F</td><td>5.50±0.10</td></tr> <tr><td>A0</td><td>3.86±0.15</td></tr> <tr><td>B0</td><td>5.65±0.10</td></tr> <tr><td>K0</td><td>2.75±0.15</td></tr> <tr><td>T</td><td>0.25±0.05</td></tr> </table>	Symbol	Dimension (mm)	W	12.00±0.20	P0	4.00±0.10	P1	8.00±0.10	P2	2.00±0.10	D0	Φ1.55±0.10	D1	Φ1.5±0.10	E	1.75±0.10	F	5.50±0.10	A0	3.86±0.15	B0	5.65±0.10	K0	2.75±0.15	T	0.25±0.05
Symbol	Dimension (mm)																										
W	12.00±0.20																										
P0	4.00±0.10																										
P1	8.00±0.10																										
P2	2.00±0.10																										
D0	Φ1.55±0.10																										
D1	Φ1.5±0.10																										
E	1.75±0.10																										
F	5.50±0.10																										
A0	3.86±0.15																										
B0	5.65±0.10																										
K0	2.75±0.15																										
T	0.25±0.05																										
7" Reel 	<table> <tr><td>D2</td><td>Φ178.0±2.0</td></tr> <tr><td>D3</td><td>Φ50.0Min.</td></tr> <tr><td>D4</td><td>Φ13.0±0.5</td></tr> <tr><td>W1</td><td>16.0±2.0</td></tr> <tr><td colspan="2">Quantity: 500PCS</td></tr> </table>	D2	Φ178.0±2.0	D3	Φ50.0Min.	D4	Φ13.0±0.5	W1	16.0±2.0	Quantity: 500PCS																	
D2	Φ178.0±2.0																										
D3	Φ50.0Min.																										
D4	Φ13.0±0.5																										
W1	16.0±2.0																										
Quantity: 500PCS																											
13" Reel 	<table> <tr><td>D5</td><td>Φ330.0±2.0</td></tr> <tr><td>D6</td><td>Φ13.5±0.5</td></tr> <tr><td>H</td><td>2.5±1.0</td></tr> <tr><td>W2</td><td>16.0±2.0</td></tr> <tr><td colspan="2">Quantity: 3000PCS</td></tr> </table>	D5	Φ330.0±2.0	D6	Φ13.5±0.5	H	2.5±1.0	W2	16.0±2.0	Quantity: 3000PCS																	
D5	Φ330.0±2.0																										
D6	Φ13.5±0.5																										
H	2.5±1.0																										
W2	16.0±2.0																										
Quantity: 3000PCS																											

Please Read Carefully

Thank you for using or about to use our company's products. We suggest that you carefully read this material before use.

- Our company strives to provide users with higher quality products and services.
- Jiangsu POWERSi Microelectronics Co., Ltd. will periodically optimize its products and corresponding specifications, and may not be able to notify you in a timely manner. Please download the latest version regularly.
- Jiangsu POWERSi Microelectronics Co., Ltd. assumes no responsibility or risk for any use of its products for special purposes.
- Jiangsu POWERSi Microelectronics Co., Ltd. holds patent rights for its own products.
- Any semiconductor product has a certain possibility of failure or malfunction under specific conditions. The buyer is requested to comply with safety standards and take safety measures when using products from Jiangsu POWERSi Microelectronics Co., Ltd. for system design and complete machine manufacturing, in order to avoid situations that may cause personal injury or property damage!